



A rubber traction-top belt with a heavy "roebbling" cloth impression finish for moving cartons, boxes, bags etc. On inclines or declines up to 35°.

The uncoated fabric back is ideal on slider bed applications and offers high load carrying capacity, extended life and excellent performance.

Belt Construction

Number of fabrics	2	
Fabric material	Polyester	
Top cover material	Premium Ruber	
Top cover thickness	4.0 mm	0.157 in
Top cover profile	Heavy Roebbling Pattern	
Top cover colour	Black	
Top cover hardness		
Bottom cover material	Low Friction - Dry back	
Bottom cover thickness	0.0 mm	0.0 in
Bottom cover profile	Fabric	

Technical Data

Thickness	5.5 mm	0.216 in
Weight	4.5 kg/m ²	0.925 lbs/ft ²
Tensile strength for 1% elongation	n/mm	lbs/in
Minimum pulley diameter	100 mm	3.937 in
Minimum pulley back flex diameter	mm	in
Minimum temperature	-20 °C	15 °F
Maximum temperature	80 °C	185 °F
Maximum width	1800mm	70.86 in

Characteristics

Slider Bed	Yes
Carry Rollers	Yes
Troughed	Yes
Food Quality	No
Oil and Fat Resistant	No
Flame Retardant	No
Anti Static	Yes

Due to our continuous search for improvement, the above data is subject to alteration. This data replaces any previous publications. Apex Belting Ltd excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale, are all activities performed and services rendered by Apex Belting Ltd

APEX BELTING LTD

Boldero Road, Moreton Hall Industrial Estate,
 Bury St. Edmunds, Suffolk IP32 7BS. England.

Tel: 01284 752486
Fax: 01284 750542

E-mail: sales@apexbelting.co.uk
Website: www.apexbelting.co.uk