



A truly multi purpose belt of the highest quality the versatility of this belt finds it being used in a variety of applications from package handling to industrial and agricultural uses. The design construction of this belt offers higher unit strength and load carrying capacity, extended life and excellent performance. This construction provides the following; Moderately Oil Resistant, Exceptional wear resistance, Minimum stretch, Directional stability, Troughable, Excellent weather resistance and manufactured to BS490:1

Belt Construction

Number of fabrics	3	
Fabric material	Polyester/ Polyamide	
Top cover material	SBR/NBR Moderately Oil Resistant Rubber	
Top cover thickness	3.0 mm	0.118 in
Top cover profile	Smooth	
Top cover colour	Black	
Top cover hardness	60 Shore A	
Bottom cover material	Low Friction - Dry Back	
Bottom cover thickness	0.0 mm	0.000 in
Bottom cover profile	Fabric	

Technical Data

Thickness	6.5 mm	0.256 in
Weight	7.50 kg/m ²	1.537 lbs/ft ²
Nominal Tensile Strength	400 n/mm	2235.89 lbs/in
Minimum pulley diameter	150 mm	0.236 in
Minimum pulley back flex diameter	175 mm	6.890 in
Minimum temperature	-20 °C	-4 °F
Maximum temperature	80 °C	176 °F
Maximum width	3000 mm	118.110 in

Characteristics

Slider Bed	Yes
Carry Rollers	Yes
Troughed	Yes
Food Quality	No
Oil and Fat Resistant	Yes MOR
Flame Retardant	No
Anti Static	Yes

Due to our continuous search for improvement, the above data is subject to alteration. This data replaces any previous publications. Apex Belting Ltd excludes any liability for the incorrect use of the above stated information. All activities performed and services rendered by Apex Belting Ltd are subject to the general terms and conditions of sale.

APEX BELTING LTD

Boldero Road, Moreton Hall Industrial Estate,
Bury St. Edmunds, Suffolk IP32 7BS. England.

Tel: 01284 752486
Fax: 01284 750542

E-mail: sales@apexbelting.co.uk
Website: www.apexbelting.co.uk