



A high quality 3 Ply Rubber Belt for Transporting moderately abrasive materials. Widely used in the agricultural industry for conveying all types of produce, this construction provides the following properties; High wear resistance, Minimum stretch, High impact Resistance, Directional Stability, Good Weather Resistance and manufactured to BS490:1

Belt Construction

Number of fabrics	3	
Fabric material	Polyester/ Polyamide	
Top cover material	SBR Rubber	
Top cover thickness	3.0 mm	0.118 in
Top cover profile	Smooth	
Top cover colour	Black	
Top cover hardness	60 Shore A	
Bottom cover material	SBR Rubber	
Bottom cover thickness	1.5 mm	0.059 in
Bottom cover profile	Smooth	

Technical Data

Thickness	8 mm	0.315 in
Weight	8.40 kg/m ²	1.721 lbs/ft ²
Nominal Tensile Strength	400 n/mm	2235.89 lbs/in
Minimum pulley diameter	315 mm	0.236 in
Minimum pulley back flex diameter	250 mm	9.843 in
Minimum temperature	-20 °C	-4 °F
Maximum temperature	80 °C	176 °F
Maximum width	2600 mm	102.362 in

Characteristics

Slider Bed	No
Carry Rollers	Yes
Troughed	Yes
Food Quality	No
Oil and Fat Resistant	No
Flame Retardant	No
Anti Static	Yes

Due to our continuous search for improvement, the above data is subject to alteration. This data replaces any previous publications. Apex Belting Ltd excludes any liability for the incorrect use of the above stated information. All activities performed and services rendered by Apex Belting Ltd are subject to the general terms and conditions of sale.

APEX BELTING LTD

Boldero Road, Moreton Hall Industrial Estate,
Bury St. Edmunds, Suffolk IP32 7BS. England.

Tel: 01284 752486
Fax: 01284 750542

E-mail: sales@apexbelting.co.uk
Website: www.apexbelting.co.uk