



An high quality, medium duty conveyor belt designed for use in Logistics, Warehouse distribution and many other applications. The smooth Satin finish on the carrying surface is ideal for accumulation applications. The 2 ply construction consists of continuous polyester warp and monofilament weft giving the belt good directional stability.

Belt Construction

Number of fabrics	2	
Fabric material	Polyester/Monofilament	
Top cover material	PVC	
Top cover thickness	0.5 mm	0.020 in
Top cover profile	Satin	
Top cover colour	Black	
Top cover hardness	60 Shore A	
Bottom cover material	Fabric	
Bottom cover thickness	0.0 mm	0.000 in
Bottom cover profile	Low Friction Back	

Technical Data

Thickness	2 mm	0.079 in
Weight	2.40 kg/m ²	0.492 lbs/ft ²
Tensile strength for 1% elongation	8 n/mm	44.72 lbs/in
Minimum pulley diameter	25 mm	0.236 in
Minimum pulley back flex diameter	50 mm	1.969 in
Minimum temperature	-10 °C	14 °F
Maximum temperature	80 °C	176 °F
Maximum width	3000 mm	118.110 in

Characteristics

Slider Bed	Yes
Carry Rollers	Yes
Troughed	No
Food Quality	No
Oil and Fat Resistant	No
Flame Retardant	No
Anti Static	Yes

Due to our continuous search for improvement, the above data is subject to alteration. This data replaces any previous publications. Apex Belting Ltd excludes any liability for the incorrect use of the above stated information. All activities performed and services rendered by Apex Belting Ltd are subject to the general terms and conditions of sale.

APEX BELTING LTD

Boldero Road, Moreton Hall Industrial Estate,
Bury St. Edmunds, Suffolk IP32 7BS. England.

Tel: 01284 752486
Fax: 01284 750542

E-mail: sales@apexbelting.co.uk
Website: www.apexbelting.co.uk