



A high quality, medium duty belt suitable for a wide range of applications in practically every industry. Ideal for moving boxes, cartons sacks etc. on inclines or declines. The polyester carcass is resistant to rot and mildew and offers low stretch with excellent tracking.

Belt Construction

Number of fabrics	2	
Fabric material	Polyester/Monofilament	
Top cover material	PVC	
Top cover thickness	0.7 mm	0.028 in
Top cover profile	Snakeskin	
Top cover colour	Grey	
Top cover hardness	60 Shore A	
Bottom cover material	Fabric	
Bottom cover thickness	0.7 mm	0.028 in
Bottom cover profile	Low friction back	

Technical Data

Thickness	2 mm	0.079 in
Weight	2.40 kg/m ²	0.492 lbs/ft ²
Tensile strength for 1% elongation	68 n/mm	380.10 lbs/in
Minimum pulley diameter	50 mm	0.236 in
Minimum pulley back flex diameter	50 mm	1.969 in
Minimum temperature	-10 °C	14 °F
Maximum temperature	80 °C	176 °F
Maximum width	2000 mm	78.740 in

Characteristics

Slider Bed	Yes
Carry Rollers	Yes
Troughed	No
Food Quality	Yes
Oil and Fat Resistant	No
Flame Retardant	No
Anti Static	Yes

Due to our continuous search for improvement, the above data is subject to alteration. This data replaces any previous publications. Apex Belting Ltd excludes any liability for the incorrect use of the above stated information. All activities performed and services rendered by Apex Belting Ltd are subject to the general terms and conditions of sale.

APEX BELTING LTD

Boldero Road, Moreton Hall Industrial Estate,
Bury St. Edmunds, Suffolk IP32 7BS. England.

Tel: 01284 752486
Fax: 01284 750542

E-mail: sales@apexbelting.co.uk
Website: www.apexbelting.co.uk