



A light to Medium duty skirting material designed by Apex Belting to stop material leaks, control dust emissions and eliminates other resulting problems such as belt damage and mistracking. The single ply makes the skirt tear resistant but also flexible and the Satin finish allows for a parallel seal with belt so No belt grooving or excessive cover wear means longer belt life.

Belt Construction

Number of fabrics	1	
Fabric material	Polyester	
Top cover material	PVC	
Top cover thickness	0.5 mm	0.020 in
Top cover profile	Smooth	
Top cover colour	Green	
Top cover hardness	70 Shore A	
Bottom cover material	PVC	
Bottom cover thickness	0.7 mm	0.028 in
Bottom cover profile	Satin	

Technical Data

Thickness	2 mm	0.079 in
Weight	2.40 kg/m ²	0.492 lbs/ft ²
Tensile strength for 1% elongation	4 n/mm	22.36 lbs/in
Minimum pulley diameter	20 mm	0.236 in
Minimum pulley back flex diameter	30 mm	1.181 in
Minimum temperature	-10 °C	14 °F
Maximum temperature	80 °C	176 °F
Maximum width	2000 mm	78.740 in

Characteristics

Slider Bed	Yes
Carry Rollers	Yes
Troughed	Yes
Food Quality	Yes
Oil and Fat Resistant	No
Flame Retardant	No
Anti Static	Yes

Due to our continuous search for improvement, the above data is subject to alteration. This data replaces any previous publications. Apex Belting Ltd excludes any liability for the incorrect use of the above stated information. All activities performed and services rendered by Apex Belting Ltd are subject to the general terms and conditions of sale.

APEX BELTING LTD

Boldero Road, Moreton Hall Industrial Estate,
Bury St. Edmunds, Suffolk IP32 7BS. England.

Tel: 01284 752486
Fax: 01284 750542

E-mail: sales@apexbelting.co.uk
Website: www.apexbelting.co.uk