



An extremely high quality light duty Conveyor belting specifically designed for the Food and Pharmaceuticals Industries. The Elasticated belt has outstanding resistance to abrasion, oils, fats, detergents and to the most aggressive cleaning procedures and are ideally suited for Metal Detector, Weighing and Labelling Applications.

Belt Construction

Number of fabrics	0	
Fabric material	N/A	
Top cover material	TPU	
Top cover thickness	1.0 mm	0.039 in
Top cover profile	Satin	
Top cover colour	Blue	
Top cover hardness	60 Shore A	
Bottom cover material	TPU Black	
Bottom cover thickness	0.2 mm	0.008 in
Bottom cover profile	Fabric Impression	

Technical Data

Thickness	1.2 mm	0.047 in
Weight	1.10 kg/m ²	0.225 lbs/ft ²
Tensile strength for 1% elongation	0.7 n/mm	3.91 lbs/in
Minimum pulley diameter	10 mm	0.236 in
Minimum pulley back flex diameter	10 mm	0.394 in
Minimum temperature	-20 °C	-4 °F
Maximum temperature	60 °C	140 °F
Maximum width	1020 mm	40.157 in

Characteristics

Slider Bed	Yes
Carry Rollers	Yes
Troughed	Yes
Food Quality	Yes
Oil and Fat Resistant	Yes
Flame Retardant	No
Anti Static	Yes

Due to our continuous search for improvement, the above data is subject to alteration. This data replaces any previous publications. Apex Belting Ltd excludes any liability for the incorrect use of the above stated information. All activities performed and services rendered by Apex Belting Ltd are subject to the general terms and conditions of sale.

APEX BELTING LTD

Boldero Road, Moreton Hall Industrial Estate,
Bury St. Edmunds, Suffolk IP32 7BS. England.

Tel: 01284 752486
Fax: 01284 750542

E-mail: sales@apexbelting.co.uk
Website: www.apexbelting.co.uk